



EC64-19 | 6-axis Collaborative Robot

EC SERIES



4kg
Payload



1900mm
Radius



± 0.05 mm
Repeatability



4.0m/s
Max TCP Speed



EC64-19

EC SERIES


Robotic Arm

Payload	4kg
Radius	1900mm
Repeatability	±0.05mm
Axis	6
Joints rotation	J1-J6 ±360°
Joints speed	J1-J2 120°/s
	J3 150°/s
	J4-J6 260°/s
Max TCP Speed	4.0 m/s
IP rating	IP54
Operating Temperature range	0-50 °C
Relative humidity	5%-95% (non-condensing)
Typical power usage	350w
Mounting	Any angle
Tool I/O connector	12 pin
Tool I/O ports	2 DI, 2 DO, 1 AI, 1 AO
Tool I/O power supply	24 V
Tool I/O communication	RS485
Footprint	Ø 200 mm
Weight	33.5kg
Material	Aluminum, Steel
Cable length	5.5m
Certifications	EN ISO 10218-1


Teach-Pendant




Size	290mm x 225mm x 118mm
Screen display size	8.1"
Resolution	1280 x 800 pixels
Material	Aluminum, Plastic
Weight	1.8 kg
Cable length	5.5 m
IP rating	IP65
Input method	Resistive touch-screen, physical buttons




EC64-19 external dimensional drawing



EC64-19 base top view



EC64-19 end flange



EC64-19 working range diagram

Controller



Size	505mm x 448mm x 245mm
Material	Aluminum, Steel
IP rating	IP44
I/O ports	16 DI, 20 DO, 2 AI, 4 AO
I/O power supply	24V; 2A (internal)
Communication ports	1 Ethernet port, 1 RS485/RS232, 1 USB 2.0
Communication protocols	TCP/IP, MODBUS TCP/RTU, EtherNet/IP, Profinet, CCLink
Power source	100-240 VAC, 50-60 Hz (M: 19-72VDC)



eliterobots.com



info@elibot.com



Elite Robots



@EliteRobotsOfficial